

S5-GC(100-125)K

Solis Three Phase Grid-Tied Inverters

Efficient

- 10 MPPTs, max. efficiency 99.0%
- > 150% DC/AC ratio
- High power tracking density 100MPPT/MW
- String current up to 16A, perfectly match large current bifacial modules

Smart

- Night SVG function
- Intelligent string monitoring, smart I-V curve scan
- Remote firmware upgrade with simple operation

Safe

- IP66
- AFCI protection, proactively reduces fire risk
- Nighttime PID recovery function (optional)
- Overvoltage load reduction and leakage current suppression technology, low failure rate

Economic

- Power line communication (PLC) (optional)
- DC side supports "Y" connector

Models:

S5-GC100K

S5-GC110K

S5-GC125K-HV



DATASHEET

Models	100K	110K	125K-HV
Input DC			
Max. input voltage	1100 V		
Rated voltage	600 V		720 V
Start-up voltage	195 V		
MPPT voltage range	180 - 1000 V		
Max. input current	10 × 32 A		
Max. short circuit current	10 × 40 A		
MPPT number / Max. input strings number	10 / 20		
Output AC			
Rated output power	100 kW	110 kW	125 kW
Max. apparent output power	110 kVA	121 kVA	137.5 kVA
Max. output power	110 kW	121 kW	137.5 kW
Rated grid voltage	3/N/PE, 220 V / 380 V, 230 V / 400 V		3/PE, 480 V
Rated grid frequency	50 Hz / 60 Hz		
Rated grid output current	152.0 A / 144.3 A	167.1 A / 158.8 A	150.4 A
Max. output current	167.1 A	183.8 A	165.4 A
Power factor	> 0.99 (0.8 leading - 0.8 lagging)		
THDi	< 3%		
Efficiency			
Max. efficiency	98.7%		99.0%
EU efficiency	98.3%		98.6%
Protection			
DC reverse-polarity protection	Yes		
Short circuit protection	Yes		
Output over current protection	Yes		
Surge protection	DC Type II / AC Type II (AC Type I optional)		
Grid monitoring	Yes		
Anti-islanding protection	Yes		
Temperature protection	Yes		
Strings monitoring	Yes		
I/V Curve scanning	Yes		
Integrated AFCI 2.0	Optional		
Integrated PID recovery	Optional		
Integrated DC switch	Yes		
Integrated AC switch	Optional		
General Data			
Dimensions (W × H × D)	1065 × 567 × 344.5 mm		
Weight	91 kg		
Topology	Transformerless		
Self-consumption (night)	< 2 W		
Operating ambient temperature range	-30 ~ +60°C		
Relative humidity	0 - 100%		
Ingress protection	IP66		
Cooling concept	Intelligent fan-cooling		
Max. operation altitude	4000 m		
Grid connection standard	VDE-AR-N 4105, VDE-AR-N 4110, VDE V 0124, VDE V 0126-1-1, UTE C15-712-1, NRS 097-1-2, G98, G99, EN 50549-1/-2, RD 1699, TOR, UNE 206006, UNE 206007-1, CEI 0-21, IEC61727, DEWA		
Safety / EMC standard	IEC/EN 62109-1/-2, IEC/EN 61000-6-1/-2/-3/-4		
Features			
DC connection	MC4 connector		
AC connection	OT terminal (max. 185 mm²)		
Display	LCD		
Communication	RS485, Optional: Wi-Fi, GPRS, PLC		