



Sigen Energy Controller

5.0 – 30.0 kW Three Phase

- EMS inside for precise control
- Up to 4 MPP. trackers
- Multi-source black start
- On & off-grid compatibility
- DC/AC ratio up to 16
- IP66 system protection rating

Sigen Energy Controller 5.0–30.0 kW Three Phase ¹

SigenStor EC	5.0 TP	6.0 TP	8.0 TP	10.0 TP	12.0 TP	15.0 TP	17.0 TP	20.0 TP	25.0 TP	30.0 TP	Units
DC Input (from PV)											
Max. PV power	8000	9600	12800	16000	19200	24000	27200	32000	40000	48000	W
Max. DC input voltage	1100										V
Nominal DC input voltage	600										V
Start-up voltage	180										V
MPPT voltage range	160 ~ 1000										V
Number of MPP trackers	2			3			4				
Number of PV strings per MPPT	1										
Max. input current per MPPT	16										A
Max. short-circuit current per MPPT	20										A
AC Output (on-grid)											
Nominal output power	5000	6000	8000	10000	12000	15000	17000	20000	25000	30000	W
Max. output apparent power	5500	6600	8800	11000	13200	16500	18700	22000	27500	33000	VA
Nominal output current	7.6	9.1	12.2	15.2	18.2	22.8	25.8	30.4	38.0	45.5	A
Max. output current	8.4	10.0	13.4	16.7	20.1	25.1	28.4	33.4	41.8	50.0	A
Nominal output voltage	380 / 400										V
Nominal grid frequency	50 / 60										Hz
Power factor	0.8 leading ~ 0.8 lagging										
Total current harmonic distortion	THDi < 2%										
Efficiency											
Max. efficiency	98.1%	98.2%	98.3%	98.3%	98.3%	98.3%	98.3%	98.3%	98.3%	98.4%	
European efficiency	96.1%	96.6%	97.1%	97.5%	97.7%	97.9%	97.9%	97.9%	98.0%	98.0%	
AC Output (backup)											
Peak output power (10 seconds)	7500	9000	12000	15000	18000	22500	25500	30000	30000	36000	W
Nominal output voltage	380 / 400										V
Nominal output frequency	50 / 60										Hz
Power factor	0.8 leading ~ 0.8 lagging										
Total voltage harmonic distortion	THDv < 2%										
Disruption time of backup switch ²	0										ms
Battery Connection											
Battery module models	SigenStor BAT 5.0 / 8.0										
Number of modules per controller	1 ~ 6										pcs
Battery module voltage range	600 ~ 900										V
Protection											

General Data

Dimensions (W / H / D)	700 / 300 / 260	mm
Weight	36	kg
Storage temperature range	-40 ~ 70	°C
Operating temperature range	-30 ~ 60	°C
Relative humidity range	0% ~ 95%	
Max. operating altitude	4000	m
Cooling	Smart air cooling	
System ingress protection rating	IP66	
Communication	WLAN / Fast Ethernet / RS485 / Sigen CommMod (4G/3G/2G)	

Standard Compliance

Standard ⁴	IEC/EN 62109-1, IEC/EN 62109-2, IEC/EN 61000-6-1, IEC/EN 61000-6-2
-----------------------	--

- Sigen Energy Controller 30.0 kW Three Phase is only available in specific regions. Please contact Sigenenergy or local distributors for details.
- This refers to the load-side disruption time, to achieve this functionality Sigen Energy Gateway needs to be used together with Sigen Energy Controller and Sigen Battery. Test conditions: In the open-circuit state of the power grid, the nominal power of the Sigen Energy Controller is higher than the total power of the home loads.
- This is an optional feature only supported in certain models, please contact Sigenenergy for more information.
- For all standards refer to the certificates category on the Sigenenergy website.

Disclaimer: The information in this file is provided on an "as is" basis. To the fullest extent permitted by law, Sigenenergy Technology Co., Ltd. excludes all representations and warranties relating to this file and its contents or which is or may be provided by any affiliates or any other third party, including in relation to any inaccuracies or omissions in this file.



Sigen Energy Controller

3.0 – 12.0 kW Single Phase

- EMS inside for precise control
- Up to 4 MPP. trackers
- Multi-source black start
- On & off-grid compatibility
- DC/AC ratio up to 2
- IP66 system protection rating

Sigen Energy Controller 3.0–12.0 kW Single Phase ¹

SigenStor EC	3.0 SP	3.6 SP	4.0 SP	4.6 SP	5.0 SP	6.0 SP	8.0 SP	10.0 SP	12.0 SP	Units
DC Input (from PV)										
Max. PV power	6000	7360	8000	9200	10000	12000	16000	20000	24000	W
Max. DC input voltage	600									V
Nominal DC input voltage	350									V
Start-up voltage	100									V
MPPT voltage range	50 ~ 550									V
Number of MPP trackers	2						3	4	4	
Number of PV strings per MPPT	1									
Max. input current per MPPT	16									A
Max. short-circuit current per MPPT	20									A
AC Output (on-grid)										
Nominal output power	3000	3680	4000	4600	5000	6000	8000	10000	12000	W
Max. output apparent power	3300	3680	4400	5000	5500	6600	8800	11000	12000	VA
Nominal output current	13.6	16.0	18.2	20.9	22.7	27.3	36.4	45.5	54.6	A
Max. output current	15.0	16.0	20.0	22.7	25.0	30.0	40.0	50.0	54.6	A
Nominal output voltage	220 / 230 / 240						220 / 230			V
Nominal grid frequency	50 / 60									Hz
Power factor	0.8 leading ~ 0.8 lagging									
Total current harmonic distortion	THDi < 2%									
Efficiency										
Max. efficiency	98.0%	98.0%	98.0%	98.0%	98.0%	98.0%	97.6%	97.6%	97.6%	
European efficiency	97.0%	97.1%	97.2%	97.3%	97.4%	97.4%	97.0%	97.0%	97.0%	
AC Output (backup)										
Peak output power (10 seconds)	4500	5520	6000	6900	7500	9000	12000	15000	15000	W
Nominal output voltage	220 / 230 / 240						220 / 230			V
Nominal output frequency	50 / 60									Hz
Power factor	0.8 leading ~ 0.8 lagging									
Total voltage harmonic distortion	THDv < 2%									
Disruption time of backup switch ²	0									ms
Battery Connection										
Battery module models	SigenStor BAT 5.0 / 8.0									
Number of modules per controller	1 ~ 6									pcs
Battery module voltage range	300 ~ 600									V
Protection										
Safety protection feature	DC reverse polarity protection, Insulation monitoring, Residual current monitoring, Arc fault circuit interrupter ³ , AC overcurrent/overvoltage/short-circuit protection. Type II DC/AC surge protection, Anti-islanding protection									

General Data

Dimensions (W / H / D)	700 / 300 / 245	700 / 300 / 260	mm
Weight	18	36	kg
Storage temperature range	-40 ~ 70		°C
Operating temperature range	-30 ~ 60		°C
Relative humidity range	0% ~ 95%		
Max. operating altitude	4000		m
Cooling	Natural convection	Smart air cooling	
System ingress protection rating	IP66		
Communication	WLAN / Fast Ethernet / RS485 / Sigen CommMod (4G/3G/2G)		

Standard Compliance

Standard ⁴	IEC/EN 62109-1, IEC/EN 62109-2, IEC/EN 62477, IEC/EN 61000-6-1, IEC/EN 61000-6-2
-----------------------	--

- Sigen Energy Controller 8.0–12.0 kW Single Phase is only available in specific regions. Please contact Sigenenergy or local distributors for details.
- This refers to the load-side disruption time, to achieve this functionality Sigen Energy Gateway needs to be used together with Sigen Energy Controller and Sigen Battery. Test conditions: In the open-circuit state of the power grid, the nominal power of the Sigen Energy Controller is higher than the total power of the home loads.
- This is an optional feature only supported in certain models, please contact Sigenenergy for more information.
- For all standards refer to the certificates category on the Sigenenergy website.

Disclaimer: The information in this file is provided on an "as is" basis. To the fullest extent permitted by law, Sigenenergy Technology Co., Ltd. excludes all representations and warranties relating to this file and its contents or which is or may be provided by any affiliates or any other third party, including in relation to any inaccuracies or omissions in this file.